

Electricals Ltd.

TECHNICAL DATA SHEET

FORM No. DSG/FR/08


Doc Classification:

Restricted-4

Division: Lighting

Department: Design and Development

Document Number: TD0901332 Page 1 of 3 Revision: Issue No. 1 Date: 13/11/2021 Issue Date:02-05-2018



DIMENSIONS SHOWN ARE FOR INSTALLATION REFERENCES ONLY AND WILL HAVE TOLERANCE ±3mm UNLESS OTHERWISE SPCIFIED

GENERAL:

This streetlight luminaire comprises of die cast aluminium housing with IP66 lens module. This luminaire is recommended for illuminating access roads, traffic routes etc.

PRODUCT DESCRIPTION	**NOMINAL WATTAGE	ССТ	CRI	VOLTAGE	**MAINS CURRENT	*APPROX WT
	(W)	(K)		(V)	(A)	(KG)
TRP-417-45-57-SL-LM-NBK	45	5700 ANSI	70	240	0.197	1.30
Efficacy > 100LPW						

^{*}ONLY FOR STRUCTURAL/MOUNTING DESIGN CONSIDERATION

CONTROLLED COPY IF STAMPED IN RED

VALIDITY: UNTIL NEXT REVISION DESIGN & DEVELOPMENT DEPT.

CUSTOMER REFERENCE: TITLE: 45W LED STREETLIGHT TYPE: TRP STAMP: PREPARED BY **CHECKED BY** APPROVED BY ganesh.dhuri

Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN

- 2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION **IN WRITING**
- 3.THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
- 4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF +/-3mm UNLESS OTHERWISE SPECIFIED

^{**}RATED SYSTEM WATTAGE AND CURRENT WILL HAVE TOLERANCE AS PER IS 16104: 2012



TECHNICAL DATA SHEET

FORM No. DSG/FR/08
Doc Classification:
Restricted-4

Division: Lighting

Department: Design and Development

	Restricted-4
Document Number: TD0901332	Page 2 of 3
Revision:	Issue No. 1
Date: 13/11/2021	Issue Date:02-05-2018

MATERIAL SPECIFICATIONS:	
Housing	Aluminium Die cast powder coated in Matt Black
IP Lens Module	Polycarbonate
Internal Wiring	PVC coated multistrand wire
Cable	3 Core PVC coated multistrand cable.
Surge Arrestor	4 KV inbuilt in Driver

ELECTRICAL PARAMETERS:		
Rated Voltage (V)	240	
Frequency (Hz)	50 ±3	
Operating Voltage Range (V)	120 – 270~	
Current (A) @ 240V	0.197	
Wattage (W) @240V	45	
P.F.	≧ 0.95	
I THD	< 10%	

CONTROLLED COPY

IF STAMPED IN RED

VALIDITY: UNTIL NEXT REVISION
DESIGN & DEVELOPMENT DEPT.

TITLE: 45W LED STREETLIGHT	TYPE: T	RP	CUSTOMER REFERENCE:		STAMP:
PREPARED BY ganesh.dhuri		CHECKED BY		APPRO	VED BY

Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN

- 2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING
- 3.THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
- 4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF +/-3mm UNLESS OTHERWISE SPECIFIED



TECHNICAL DATA SHEET

FORM No. DSG/FR/08
Doc Classification:
Restricted-4

Division: Lighting

Department: Design and Development

	1 tootholog 1
Document Number: TD0901332	Page 3 of 3
Revision:	Issue No. 1
Date: 13/11/2021	Issue Date:02-05-2018

INSTALLATION:	
Mounting System	Suitable for 30 to 40 mm max. O.D. mounting pipe.
Protection	IP 66

PRODUCT ORDERING CODE:				
Product Description	Ordering Code			
TRP-417-45-57-SL-LM-NBK	TLR400230-E4			

SPARES ORDERING REFERENCE:					
Product Description	Driver				
TRP-417-45-57-SL-LM-NBK	45W @700mA S0DVEXC4-45W-700				

CONTROLLED COPY

IF STAMPED IN RED

VALIDITY: UNTIL NEXT REVISION
DESIGN & DEVELOPMENT DEPT.

TITLE: 45W LED STREETLIGHT	TYPE: T	RP	CUSTOMER REFERENCE:		STAMP:
PREPARED BY ganesh.dhuri		CHECKED BY		APPRO	VED BY

Note: 1 AS EFFORTS ARE ON CONSTANTLY TO IMPROVE THE DESIGN AND METHODS OF MANUFACTURE OF THE PRODUCT, THE PRODUCT SUPPLIED MAY DIFFER IN DETAIL FROM THE DATA GIVEN HERE IN

- 2. THIS DRAWING & DESIGN IS THE PROPERTY OF CROMPTON GREAVES CONSUMER ELECTRICALS LTD. AND MUST NOT BE COPIED OR LENT WITHOUT THEIR PERMISSION IN WRITING
- 3.THE "APPROVED" INDICATED THAT IT IS A CONTROL COPY
- 4. DIMENSION SHOWN ARE FOR INSTALLATION REFERENCE ONLY AND IN MM WITH TOLERANCE OF +/-3mm UNLESS OTHERWISE SPECIFIED